



# KRY BEARING AFRICA PRIVATE LTD.



## QM INDUSTRIES QACW15A070SEM Flange Block Bearings

Bearing No. QACW15A070SEM

QACW15A070SEM Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Flange Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.988  |
| EAN                       | 0883450305549  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Round Flange Cartridge  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215  |
| Seals                     | Triple Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch - Metric             | Metric   |
| Long Description          | 4 Bolt Round Flange Cartridge; 70MM Bore; 190MM Bolt Circle; 134.7MM Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Steel; Spherical Roller Bearing; |



## KRY BEARING AFRICA PRIVATE LTD.

|                                    |   |
|------------------------------------|---|
|                                    | 91.948MM Length Thru Bore; Relubricatab                           |
| Other Features                     | Double Row   Single Collar   With Set Screw                       |
| Category                           | Flange Block  |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.80   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Manufacturer URL                   | <a href="http://www.qmbearings.com">http://www.qmbearings.com</a> |
| Weight / LBS                       | 22  |
| Bolt Spacing                       | 5.3 Inch   134.7 Millimeter                                       |
| Cartridge Pilot Diameter           | 6.457 Inch   164 Millimeter                                       |
| Nominal Bolt Circle Diameter Round | 7.5 Inch   190 Millimeter   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter   |
| D                                  | 3.62 Inch   91.948 Millimeter                                     |
| d                                  | 2.756 Inch   70 Millimeter  |