



KRY BEARING AFRICA PRIVATE LTD.



2.362 Inch | 60 Millimeter x 4.331 Inch | 110
Millimeter x 0.866 Inch | 22 Millimeter SKF 6212
TC/C782 Precision Ball Bearings

Bearing No. 6212 TC/C782

6212 TC/C782 Bearing 2D drawings and 3D CAD
models

| | |
|----------------------|--|
| Category | Precision Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.813 |
| EAN | 7316576606441 |
| Product Group | B04270 |
| Enclosure | Open |
| Precision Class | ABEC 5 ISO P5 |
| Material - Ball | Steel |
| Number of Bearings | 1 (Single) |
| Contact Angle | 0 Degree |
| Preload | None |
| Raceway Style | Not Applicable |
| Cage Material | Phenolic |
| Rolling Element | Ball Bearing |
| Flush Ground | No |
| Inch - Metric | Metric |
| Other Features | Single Row Deep Groove Inner Ring Guided |
| Long Description | 60MM Bore; 110MM Outside Diameter; 22MM Width; Open Enclosure; ABEC 5 ISO P5 Precision; Steel Ball Material; 1 (Single) Bearings; 0 Degree Contact Angle; Phenolic |



KRY BEARING AFRICA PRIVATE LTD.

| | |
|--------------------------|---|
| | Cage Material; Ball Bearing |
| Category | Precision Ball Bearings |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Deep Groove Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 6212 TC/C782 |
| Weight / LBS | 1.79 |
| d | 2.362 Inch 60 Millimeter |
| D | 4.331 Inch 110 Millimeter |
| B | 0.866 Inch 22 Millimeter |
| bore diameter: | 60 mm |
| static load capacity: | 36 kN |
| outside diameter: | 110 mm |
| precision rating: | Not Rated |
| overall width: | 22 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Open |
| outer ring width: | 22 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| fillet radius: | 1.5 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm: | 8000 RPM |
| internal clearance: | C0 |
| series: | 62 |
| dynamic load capacity: | 55.3 kN |