



KRY BEARING AFRICA PRIVATE LTD.



239/560 CA/C083W507 Bearing 2D drawings and 3D CAD models

22.047 Inch | 560 Millimeter x 29.528 Inch | 750 Millimeter x 5.512 Inch | 140 Millimeter SKF 239/560 CA/C083W507 Spherical Roller Bearings

Bearing No. 239/560 CA/C083W507

| | |
|---------------------------|--|
| Category | Spherical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 217.7 |
| EAN | 7316570016932 |
| Product Group | B04311 |
| Internal Clearance | C3-Loose |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Bronze |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Withdrawal Nut | Not Applicable |
| Inch - Metric | Metric |
| Long Description | 560MM Straight Bore; 750MM Outside Diameter; 140MM Width; C3-Loose Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable |
| Category | Spherical Roller Bearing |



KRY BEARING AFRICA PRIVATE LTD.

| | |
|------------------------------|---|
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer URL | http://www.skf.com |
| Weight / LBS | 479.505 |
| D | 29.528 Inch 750 Millimeter |
| B | 5.512 Inch 140 Millimeter |
| d | 22.047 Inch 560 Millimeter |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| bore diameter: | 560 mm |
| maximum rpm: | 850 RPM |
| outside diameter: | 750 mm |
| operating temperature range: | Maximum of +390 ° F |
| overall width: | 140 mm |
| cage material: | Brass |
| bore type: | Straight |
| bearing material: | Steel |
| outer ring type: | Not Split |
| cage type: | Inner Ring Guided |
| internal clearance: | C083 |
| precision rating: | Not Rated |
| closure type: | Open |
| finish/coating: | Uncoated |
| lubrication hole type: | Lubrication Groove & Hole |
| outer ring width: | 140 mm |
| dynamic load capacity: | 3450 kN |
| fillet radius: | 4 mm |
| static load capacity: | 7200 kN |
| series: | 239 |